


## DB M 1 255 FM (961 125)


- Coordinated spark-gap-based lightning current arrester consisting of a base part and plug-in protection module
- Maximum system availability due to RADAX Flow follow current limitation
- Without additional cable length directly coordinated with DEHNguard surge protective device



Figure without obligation



Basic circuit diagram DB M 1 255 FM



Dimension drawing DB M 1 255 FM

Coordinated modular single-pole lightning current arrester with high follow current limitation; with remote signalling contact for the monitoring system (floating changeover contact)

Type	DB M 1 255 FM
Part No.	961 125
SPD according to EN 61643-11	Type 1
SPD according to IEC 61643-1/-11	Class I
Max. continuous operating a.c. voltage (U <sub>C</sub> )	255 V
Lightning impulse current (10/350 μs) (I <sub>imp</sub> )	50 kA
Specific energy (W/R)	625.00 kJ/ohms
Nominal discharge current (8/20 μs) (I <sub>n</sub> )	50 kA
Voltage protection level (U <sub>P</sub> )	≤ 2.5 kV
Follow current extinguishing capability a.c. (I <sub>fi</sub> )	50 kA <sub>rms</sub>
Follow current limitation/Selectivity	no tripping of a 32 A gL/gG fuse up to 50 kA <sub>rms</sub> (prosp.)
Response time (t <sub>a</sub> )	≤ 100 ns
Max. backup fuse (L) up to I <sub>K</sub> = 50 kA <sub>rms</sub> (t <sub>a</sub> ≤ 0.2 s)	500 A gL/gG
Max. backup fuse (L) up to I <sub>K</sub> = 50 kA <sub>rms</sub> (t <sub>a</sub> ≤ 5 s)	315 A gL/gG
Max. backup fuse (L-L')	125 A gL/gG
Temporary overvoltage (TOV) (U <sub>T</sub> )	440 V / 5 sec.
TOV characteristic	withstand
Operating temperature range (parallel connection) (T <sub>UP</sub> )	-40°C...+80°C
Operating temperature range (series connection) (T <sub>US</sub> )	-40°C...+60°C
Operating state/fault indication	green / red
Number of ports	1
Cross-sectional area (L/N, L'/N', N/PE (N)) (min.)	10 mm <sup>2</sup> solid/flexible
Cross-sectional area (L/N, N/PE(N)) (max.)	50 mm <sup>2</sup> stranded/35 mm <sup>2</sup> flexible
Cross-sectional area (L'/N') (max.)	35 mm <sup>2</sup> stranded/25 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	2 module(s), DIN 43880
Approvals	VDE, KEMA, UL
Type of remote signalling contact	changeover contact
a.c. switching capacity	250 V/0.5 A
d.c. switching capacity	250 V/0.1 A; 125 V/0.2 A; 75 V/0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid/flexible
<b>Extended technical data:</b>	<b>Use in installations with prospective short-circuit currents of more than 50 kA<sub>rms</sub> (tested by VDE)</b>
– Maximum prospective short-circuit current	100 kA <sub>rms</sub> (220 kA <sub>peak</sub> )
– Limitation/extinction of mains follow currents	up to 100 kA <sub>rms</sub> (220 kA <sub>peak</sub> )
– Max. backup fuse (L) up to I <sub>K</sub> = 100 kA <sub>rms</sub> (t <sub>a</sub> ≤ 0.2 s)	500 A gL/gG
– Max. backup fuse (L) up to I <sub>K</sub> = 100 kA <sub>rms</sub> (t <sub>a</sub> ≤ 5 s)	315 A gL/gG
Weight	343 g
Customs tariff number	85363030
GTIN	4013364118621
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.